P-Channel Enhancement Mode Vertical DMOS FETs

Features

- Low threshold — -2.4V max.
- High input impedance
- Low input capacitance — 125pF max.
- Fast switching speeds
- Low ON-resistance
- Free from secondary breakdown
- Low input and output leakage
- Complementary N and P-channel devices

Applications

- Logic level interfaces – ideal for TTL and CMOS
- Solid state relays
- Battery operated systems
- Photo voltaic drives
- Analog switches
- General purpose line drivers
- Telecom switches

General Description

This low threshold enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Ordering Information

BV_{DSS}/BV_{DGS} (V)	$R_{DS(ON)}$ max (Ω)	$V_{GS(th)}$ max (V)	$I_{D(ON)}$ min (A)	Package Option
				TO-243AA (SOT-89)
-200	12	-2.4	-0.75	TN2520N8-G

-G indicates package is RoHS compliant ('Green')

Absolute Maximum Ratings

Parameter	Value
Drain-to-source voltage	BV_{DSS}
Drain-to-gate voltage	BV_{DGS}
Gate-to-source voltage	±20V
Operating and storage temperature	-55°C to +150°C
Soldering temperature*	300°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

** Distance of 1.6 mm from case for 10 seconds.*

Pin Configuration



TO-243AA (SOT-89) (N8)

Product Marking

W = Code for week sealed

TO-243AA (SOT-89) (N8)

Thermal Characteristics

Package	I_D (continuous)* (mA)	I_D (pulsed) (A)	Power Dissipation @ T_A = 25°C (W)	θ_{jc} °C/W	θ_{ja} °C/W	I_{DR}* (mA)	I_{DRM} (A)
TO-243AA (SOT-89)	-260	-2.0	1.6	15	78(†)	-260	-2.0

* I_D (continuous) is limited by max rated T_j .
† Mounted on FR5 board, 25mm x 25mm x 1.57mm.

Electrical Characteristics (T_A = 25°C unless otherwise specified)

Symbol	Parameter	Min	Typ	Max	Units	Conditions
BV_{DSS}	Drain-to-source breakdown voltage	-200	-	-	V	V_{GS} = 0V, I_D = -2.0mA
$V_{GS(th)}$	Gate threshold voltage	-1.0	-	-2.4	V	V_{GS} = V_{DS}, I_D= -1.0mA
$\Delta V_{GS(th)}$	Change in $V_{GS(th)}$ with temperature	-	-	4.5	mV/°C	V_{GS} = V_{DS}, I_D= -1.0mA
I_{GSS}	Gate body leakage	-	-	-100	nA	V_{GS} = ± 20V, V_{DS} = 0V
I_{DSS}	Zero gate voltage drain current	-	-	-10	µA	V_{GS} = 0V, V_{DS} = Max Rating
			-	-1.0	mA	V_{GS} = 0V, V_{DS} = 0.8 Max Rating, T_A = 125°C
$I_{D(ON)}$	ON-state drain current	-0.25	-0.7	-	A	V_{GS} = -4.5V, V_{DS} = -25V
		-0.75	-2.1	-		V_{GS} = -10V, V_{DS} = -25V
$R_{DS(ON)}$	Static drain-to-source ON-State resistance	-	10	15	Ω	V_{GS} = -4.5V, I_D = -100mA
			8.0	12		V_{GS} = -10V, I_D = -200mA
$\Delta R_{DS(ON)}$	Change in $R_{DS(ON)}$ with temperature	-	-	1.7	%/°C	V_{GS} = -10V, I_D = -200mA
G_{FS}	Forward transconductance	100	250	-	mmho	V_{DS} = -25V, I_D = -200mA
C_{ISS}	Input capacitance	-	75	125	pF	V_{GS} = 0V, V_{DS} = -25V, f = 1.0 MHz
C_{OSS}	Common source output capacitance	-	20	85		
C_{RSS}	Reverse transfer capacitance	-	10	35		
$t_{d(ON)}$	Turn-ON delay time	-	-	10	ns	V_{DD} = -25V, I_D = -0.75A, R_{GEN} = 25Ω
t_r	Rise time	-	-	15		
$t_{d(OFF)}$	Turn-OFF delay time	-	-	20		
t_f	Fall time	-	-	15		
V_{SD}	Diode forward voltage drop	-	-	-1.8	V	V_{GS} = 0V, I_{SD} = -0.5A
t_{rr}	Reverse recovery time	-	300	-	ns	V_{GS} = 0V, I_{SD} = -0.5A

Notes:
(1) All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)
(2) All A.C. parameters sample tested.

Switching Waveforms and Test Circuit



Typical Performance Curves

Output Characteristics



Saturation Characteristics



Transconductance vs. Drain Current



Power Dissipation vs. Ambient Temperature



Maximum Rated Safe Operating Area



Thermal Response Characteristics



Typical Performance Curves *(cont.)*

BV_{DSS} Variation with Temperature



On-Resistance vs. Drain Current



Transfer Characteristics



$V_{(th)}$ and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics



3-Lead TO-243AA (SOT-89) Package Outline (N8)



Top View



Side View

Symbol		A	b	b1	C	D	D1	E	E1	e	e1	H	L
Dimensions (mm)	MIN	1.40	0.44	0.36	0.35	4.40	1.62	2.29	2.13	1.50 BSC	3.00 BSC	3.94	0.89
	NOM	-	-	-	-	-	-	-	-			-	-
	MAX	1.60	0.56	0.48	0.44	4.60	1.83	2.60	2.29			4.25	1.20

JEDEC Registration TO-243, Variation AA, Issue C, July 1986.
***Drawings not to scale**.*

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell its products for use in such applications, unless it receives an adequate "product liability indemnification insurance agreement". **Supertex** does not assume responsibility for use of devices described and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the **Supertex** website: http//www.supertex.com.

©2007 **Supertex inc.** All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 222-8888 / FAX: (408) 222-4895
www.supertex.com